Vision Solar Brite Stretch



Technical Data Sheet Vision Solar Brite Stretch

Polyester textile with a brushed diffuser back, ideal for fabric tension frame systems and backlit prints.

Material 100 % Polyester

Possible widths Available up to 3100mm

Finishing Rolled on paper cores

Ecology Öko-Tex Standard 100, product class IV

Remarks Transfer Printing, direct printing with dye-sub inks

Flame retardant, elastic, wrinkle resistant, lightbox

Fire Rating EN 13501

Weight

acc. to DIN EN 12127 210.00 [g/m²] ± 3 [%]

Shrinkage

Heat Shrinkage, 195°C, 90 sec

acc. to DIN EN ISO 13934-1

Heat Shrinkage, 195°C, 90 sec

crosswise acc. to PAO_13 -1.00 [%] ± 1 [%]

Tearing Strength

Elongation at 100N, longitudinal direction acc. to DIN EN ISO 13934-1 21.00 [%] \pm 20 [%] Elongation at 100N, cross direction acc. to DIN EN ISO 13934-1 24.00 [%] \pm 20 [%] Elongation at 200 N, longitudinal direction



Roseash Limited, Unit B, The Heights, Ibstone Road, Stokenchurch, Bucks, HP14 3BG T: 01494 760 240 E: sales@dpm.com W: www.dpm.com

± 20

[%]

[%]

39.00